



- ① ANY OPEN, MISWIRING, SHORT, INTERMITTENT WIRING ARE NOT PERMITTED .
- ② INSULATION RESISTANCE : 50M OHMS / 250V DC MIN .
- ③ PIN4,5 HIGH THAN OTHERS BY 1.9MM .

**PIN OUT**

P2		P2	
6		8	GREEN
14		9	BLUE
10		11	PURPLE
2		12	GRAY
1	LIGHT BLUE	13	WHITE
3	ORANGE	15	PINK
4	BLACK	16	RED
5	BROWN		
7	YELLOW		

4	Delphi pin . packard 12047581 .
3	Outer Molded : 45P PVC , Color : Black .
2	<b>P2 conn: OBD-II Type B, Nylon 66+15% Glass fibre, UL94V-0, Black.</b>
1	Cable: UL2464 24AWG(7/0.20TC)*2PAIRS+ 24AWG(7/0.20TC) *12C + Foil Shielding OD=7.5±0.1mm, Jacket color: Black .
ITEM	DESCRIPTION

X ±	X° ±	<b>OBD2CABLES.COM</b>		
.X ±	.X° ±			
.XX ±	.XX° ±	UNITS	PART NO.	© Copyright 2008
		MM	144503	
		Property of OBD2Cables.com, cannot be used or reproduced without permission.		