



- ① ANY OPEN, MISWIRING, SHORT, INTERMITTENT WIRING ARE NOT PERMITTED .
- ② INSULATION RESISTANCE : 5M OHMS / 300V DC MIN .
- ③ PIN 4,5 HIGH THAN OTHERS BY 1.9MM .

PIN OUT

P1	P2	P3
1	1	1
2	2	2
10	10	10
16	16	16
5	5	5
6	6	6
14	14	14
7	7	7
8	8	8
9	9	9
3	3	3
11	11	11
12	12	12
13	13	13
15	15	15
4	4	4

ITEM	DESCRIPTION
5	Outer Molded : 45P PVC , Color : Black .
4	P3 TER : Delphi male pin , packard 12047581 .
3	P3 Conn: OBD-II 16P Male, Nylon66 UL94V-0, Black.
2	P1,P2 Conn : OBD F, Nylon 66+15% Glass fibre, UL94V-0, Black . with lock tap .
1	Cable: UL2464 26AWG*2PAIRS+26AWG*11C+AL/MY+D.W, Φ6.5±0.1mm, Jacket color: Black .

X ±	X ° ±		OBD2CABLES.COM	
.X ±	.X ° ±			
.XX ±	.XX ° ±	UNITS: mm	PART NO.: 145802	© Copyright 2008
				SCALE SHEET REV.
Property of OBD2Cables.com, cannot be used or reproduced without permission.				