


PINOUT

P1 BMW 20PIN	P2 OPEN	P1 BMW 20PIN	P2 OPEN
1 —————	Black	11 —————	L. red
2 —————	Brown	12 —————	L. Green
3 —————	Red	13 —————	Black & W
4 —————	Orange	14 —————	Br & W
5 —————	Yellow	15 —————	R & W
6 —————	Green	16 —————	O & W
7 —————	Blue	17 —————	Y & W
8 —————	Purple	18 —————	G & W
9 —————	Gray	19 —————	Blue & W
10 —————	White	20 —————	P & W

Testing:

- 100% open & short testing & Miss Wire
- Contact Resistance: 1 OHM
- Insulation Resistance: 5M OHM
- Dielectronic Strength: 300VDC/10MS

C	P2 Open, Cut PVC L=40mm Tin L=5mm.	20	PC
B	Cable: 26AWG*20C OD=9.0mm, L=1830mm.	1	PC
A	P1 BMW 20PIN, 45P PVC Molded, Black	1	PC
Item	SPEC	QTY	Unit

OBD2CABLES.COM		Name		BMW 20PIN to Open			
		Client		OBD-II CABLES			
DWG		Part No. 140401	© Copyright 2008	REV.	1		
Check		Date	2006.08.15	Rate	NONE		
Aped		Size	A4	Unit	mm	Page	2/6