



- ① ANY OPEN, MISWIRING & SHORT & INTERMITTENT ARE NOT PERMITTED .
- ② INSULATION RESISTANCE : 50M OHMS / 250V DC MIN .
- ③ PIN4,5 HIGH THAN OTHERS 1.9MM .

PIN OUT

P1	P2	P1	P2
1 ————— 1	1	7 ————— 7	7
2 ————X—— 2	2	8 ————— 8	8
10 ————X—— 10	10	9 ————— 9	9
3 ————— 3	3	11 ————— 11	11
4 ————— 4	4	12 ————— 12	12
5 ————— 5	5	13 ————— 13	13
6 ————X—— 6	6	15 ————— 15	15
14 ————X—— 14	14	16 ————— 16	16

5	Delphi pin .	PCS	16
4	Outer molded : 45P PVC , Color : Black .	KG	
3	P2 Conn: OBD-II 16P male , Nylon66 UL94V-0 , black .	PCS	1
2	P1 Conn : OBD F with lock , Nylon 66+15% Glass fibre, UL94V-0, Black .	PCS	1
1	Cable: UL2464 24AWG*2PAIRS+24AWG*12C+AL/MY+D.W, Φ7.5±0.1mm, Jacket color: Black .	MM	
Item	DESCRIPTION	UNIT	QTY

X ±	X ° ±	OBD2CABLES.COM		
.X ±	.X ° ±			
.XX ±	.XX ° ±	UNITS: MM	PART NO.: 144201	© Copyright 2008
		SCALE SHEET REV.		
Property of OBD2Cables.com, cannot be used or reproduced without permission.				