



- ⚠️ 1. ANY OPEN, MISWIRING & SHORT & INTERMITTENT ARE NOT PERMITTED .
- ⚠️ 2. INSULATION RESISTANCE : 50M OHMS / 250V DC MIN .
- ⚠️ 3. PIN4,5 HIGH THAN OTHERS 1.9MM .

PIN OUT

P2			P2	
6	—	CAN High (J-2284) WHITE/BLACK	8	— GREEN
14	—	CAN Low (J-2284) GREEN/BLACK	9	— BLUE
10	—	J1850 Bus - YELLOW/BLACK	11	— PURPLE
2	—	J1850 Bus + BLUE/BLACK	12	— GRAY
1	—	LIGHT BLUE	13	— WHITE
3	—	ORANGE	15	— PINK
4	—	BLACK	16	— RED
5	—	BROWN		
7	—	YELLOW		

5	DELPHI PIN , PACKARD 12047581 .	PCS	16
4	Outer molded: 45P PVC, Color: Black.	KG	
3	Overmold Strain Relief.	PCS	1
2	P1 Conn: OBD-II 16P Male, Nylon66 UL94V-0, Black.	PCS	1
1	CABLE : UL2464 24AWG(7/0.20TC)*(2Twist Pair+12C) +Paper, Jacket color: Black. OD=7.5mm .	MM	
Item	DESCRIPTION	UNIT	QTY

X ±	X° ±	OBD2CABLES.COM		
.X ±	.X° ±			
.XX ±	.XX° ±	UNITS: MM	PART NO.: 144502	© Copyright 2008
		SCALE SHEET REV.		
		Property of OBD2Cables.com, cannot be used or reproduced without permission.		