



PIN OUT

P2		P2	
6	CAN High (J-2284) WHITE/BLACK	8	GREEN
14	CAN Low (J-2284) GREEN/BLACK	9	BLUE
10	J1850 Bus - YELLOW/BLACK	11	PURPLE
2	J1850 Bus + BLUE/BLACK	12	GRAY
1	LIGHT BLUE	13	WHITE
3	ORANGE	15	PINK
4	BLACK+D.W	16	RED
5	BROWN		
7	YELLOW		

- ① ANY OPEN, MISWIRING, SHORT, INTERMITTENT WIRING ARE NOT PERMITTED .
- ② INSULATION RESISTANCE : 50M OHMS / 250V DC MIN .
- ③ PIN4,5 HIGH THAN OTHERS BY 1.9MM .

4	Delphi pin . packard 12047581 .
3	Outer Molded : 45P PVC , Color : Black .
2	P2 conn : OBD-IIA , NYLON 66+15% Glass fibre , UL94V-0 .BLACK .
1	Cable: UL2464 24AWG(7/0.20TC)*2PAIRS+ 24AWG(7/0.20TC) *12C +AL/MY+D.W , OD=7.5±0.1mm, Jacket color: Black .
ITEM	DESCRIPTION

X ±	X° ±	OBD2CABLES.COM		
.X ±	.X° ±			
.XX ±	.XX° ±	UNITS	PART NO.	© Copyright 2008
		MM	144505	
		SCALE	SHEET	REV.
Property of OBD2Cables.com, cannot be used or reproduced without permission.				